347V LED DRIVER Programmable 80W 0-10V Dimming

5-100% Output Range of 27V to 55V Current 1.05A to 2.1A Max **80W** Class 2 Short case Bottom Mount Studs with Leads

347V Electronic **Programmable (NFC)** LED Driver 0-10V Dimming **5-100%.** Output Range of 27V to 55V for Single circuit 80W maximum.

Technical Specification:

Class 2 UL, CUL Recognized, ROHS Compliant Input Voltage in EMI FCC Parts 18, Subparts C, Class A Output Load ra

Rating: TL IP 30 Damp
Output Open/Short Protection
Min. Starting Temp: 0° C
Max. Case Temp: 90° C

Max. Case Temp: 90° C Typical Efficiency 88% Input Voltage range: \pm 10%Output Load range \pm 5%Input Frequency:50/60HZTHD:< 20%Power Factor Min:0.90

Remote Wiring Distance Full Load: 18AWG -18 ft

Bottom Mount Studs

Case Size: Series FS3

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice


INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
347	0.26	91	80	27 - 55	1.05 - 2.1	PC2100C80WRBD5

LIMITED WARRANTY

5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer


Lead Length						
Colour	inch	cm				
Black	5.9	15				
White	5.9	15				
Blue	5.9	15				
Red	5.9	15				
Gray	5.9	15				

0-10V Dimmer					
Compatibility Chart					
LEVITON	LUTRON				
DS710-10Z	NFTV				
	DVTV-WH				



WARNING: Always Disconnect Power Before Handling.

Case Should be Grounded. Install in Accordance
with National and Local Electrical Codes.





Place the Programmable wand above the NFC Mark on the LED Driver to start programming

Series FS3 L W H ML
Case Size: 241mm 61 mm 37 mm 226mm
9,5inch 2.4inch 1.46inch 8.9inch

1500 Marine Drive, #200 North Vancouver, BC V7P 1T7

TEL: 604-904-9533 FAX: 604-904-9634

EMAIL: sagelighting@shaw.ca www.sagelighting.com

