347V LED DRIVER Programmable 98W 0-10V Dimming

5-100% Output Range of 27V to 55V Current 1.4A to 2.75A Max **98W** Class **2** Short case with Leads

347V Electronic **Programmable (NFC)** LED Driver 0-10V Dimming **5-100%.** Output Range of 15V to 55V for Single circuit 98W maximum.

Technical Specification:

Class 2 UL, CUL Recognized, ROHS Compliant

EMI FCC Parts 18, Subparts C, Class A

Output L

Paring: TL IR 64 Damp

Rating: **TL** IP 64 Damp Output Open/Short Protection Min. Starting Temp: 0° C

Max. Case Temp: 90° C Typical Efficiency 89% Input Voltage range: \pm 10%
Output Load range \pm 5%
Input Frequency: 50/60HZ
THD: < 20%
Power Factor Min: 0.90

Remote Wiring Distance Full Load: 18AWG -18 ft

Case Size: Series FS3

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice


INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
347	0.32	110	98	27 - 55	1.4 - 2.75	PC2750C98WRBD5

LIMITED WARRANTY

5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer


Lead Length							
Colour	inch	cm					
Black	5.9	15					
White	5.9	15					
Blue	5.9	15					
Red	5.9	15					
Gray	7.1	18					
Purple	7.1	18					

0-10V Dimmer Compatibility Chart LEVITON LUTRON DS710-10Z NFTV DVTV-WH



WARNING: Always Disconnect Power Before Handling.

Case Should be Grounded. Install in Accordance
with National and Local Electrical Codes.





Place the Programmable wand above the NFC Mark on the LED Driver to start programming

Series FS3 L W H ML Case Size: 241mm 61 mm 37 mm 226mm 9.5inch 2.4inch 1.46inch 8.9inch

1500 Marine Drive, #200 North Vancouver, BC V7P 1T7

TEL: 604-904-9533 FAX: 604-904-9634

EMAIL: sagelighting@shaw.ca www.sagelighting.com

