LED DRIVER Programmable 50W 0-10V Dimming

1-100% Output Range 15V to 55V Current 0.40A to 1.4A Max 5**0W** Small Case Size with Side leads

Universal Voltage 120-277V Electronic **Programmable (NFC)** LED Driver 0-10V Dimming **1-100%**. 1% Off at 1.4A. Output Range of 15V to 55V for Single circuit 50W maximum.

Technical Specification:

Class 2 UL, CUL Certified, ROHS Compliant EMI FCC Parts 18, Subparts C, Class A

Rating: Class P IP 64 Damp Dry_

Output Open/Short Protection

Min. Starting Temp: 0° C Max. Case Temp: 90° C

Typical Efficiency 90%

Input Voltage range: + 10%
Output Load range + 5%
Input Frequency: + 50/60HZ
THD: + 20%
Power Factor Min: + 0.90

Remote Wiring Distance Full Load: 18AWG -18 ft

Optional 1% to Off at 1.4A

Case Size: Series C1U

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice

INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
120	0.50	59	50	15 - 55	0.4 - 1.4	PU1400C50WSD
277	0.22					

LIMITED WARRANTY


5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer

Lead Length


Colour	inch	cm			
Black	5.9	15			
White	5.9	15			
Blue	5.9	15			
Red	5.9	15			
Gray	5.9	15			
Purnla	5.0	15			

0-10V Dimmer

Compatibility Chart				
LEVITON	LUTRON			
DS710-10Z	NFTV			
	DVTV-WH			




Place the Programmable wand above the NFC Mark on the LED Driver to start programming



WARNING: Always Disconnect Power Before Handling.

Case Should be Grounded. Install in Accordance
with National and Local Electrical Codes.



Series C1U L W H ML
Case Size: 133mm 63mm 30mm 123mm
5.23inch 2.48inch 1.18inch 4.84inch

1500 Marine Drive, #200 North Vancouver, BC V7P 1T7

TEL: 604-904-9533 FAX: 604-904-9634

EMAIL: sagelighting@shaw.ca www.sagelighting.com

