LED DRIVER Programmable 50W 0-10V Dimming

1-100% Output Range 15V to 55V Current 0.40A to 1.4A Max 50W

Class 2 Small Case Size - Bottom Mount Studs with leads No Mounting Flange

Universal Voltage 120-277V Electronic Programmable (NFC) LED Driver 0-10V Dimming 1-100%. Output Range of 15V to 55V for Single circuit 50W maximum.

Technical Specification:

Class 2 UL, CUL Recognized, ROHS Compliant Input Voltage range: + 10% FCC Parts 18, Subparts C, Class A Output Load range + 5% **EMI** Input Frequency: IP 64 Damp 50/60HZ Rating: TL

Output Open/Short Protection THD: < 20% Min. Starting Temp: Power Factor Min: 0.90

Max. Case Temp: 90° C Remote Wiring Distance Full Load: 18AWG -18 ft


Typical Efficiency 90% **Bottom Mount Studs**

Case Size: Series C1B

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice						2/1/17	
	INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
	120	0.50	59	50	15 - 55	0.4 - 1.4	PU1400C50WSB-D1
	277	0.22					

LIMITED WARRANTY

5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer



1500 Marine Drive, #200 North Vancouver, BC V7P 1T7

TEL: 604-904-9533 FAX: 604-904-9634

EMAIL: sagelighting@shaw.ca www.sagelighting.com

