# **120V-347V LED DRIVER 48W 0-10V Dimming**

Output Range 24V to 40V Constant Current 1200mA **Max 48W** Input leads and Output terminal blocks

Multi Voltage 120-347V Electronic Constant Current LED Driver 0-10V Dimming. Output Range of 24V to 40V for Single circuit 48W maximum.

## **Technical Specification:**

UL, CUL Certified, ROHS Compliant EMI FCC Parts 18, Subparts C, Class A

Rating: IP 30 Damp,

Output Open/Short Protection
Min. Starting Temp: - 40° C
Max. Case Temp: 90° C
Typical Efficiency: 87%

CUL US
LISTED
LED DRIVER
E337792

Input Voltage range:  $\pm$  10%
Output Load range  $\pm$  5%
Input Frequency: 50/60HZ
THD: < 20%
Power Factor Min: 0.90

Remote Wiring Distance Full Load: 18AWG -18 ft

Case Size: Series CM

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice

INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
120	0.48A	55	48	24 to 40V	1.2A	NM1200C48WSD
347	0.16A					

#### LIMITED WARRANTY


5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer

#### **Lead Length**

Colour	inch	cm
Black	3.15	8
White	3.15	8
Green	3.15	8

### 0-10V Dimmer


<b>Compatibility Chart</b>				
LEVITON	LUTRON			
DS710-10Z	NFTV			
	DVTV-WH			



Case Size: L W H ML Sereis CM 206mm 87mm 34.5mm 45mm 8.11inch 3.43inch 1.36inch 1.77inch

WARNING: Always Disconnect Power Before Handling.

Case Should be Grounded. Install in Accordance
with National and Local Electrical Codes.



1500 Marine Drive, #200 North Vancouver, BC V7P 1T7

TEL: 604-904-9533 FAX: 604-904-9634

EMAIL: sagelighting@shaw.ca www.sagelighting.com

