120V-347V LED DRIVER 54W 0-10V Dimming

Output Range 28V to 36V Constant Current 1500mA **Max 54W** Slim low profile case with terminal blocks

Multi Voltage 120-347V Electronic Constant Current LED Driver 0-10V Dimming. Output Range of 28V to 36V for Single circuit 54W maximum.

Technical Specification:

UL, CUL Certified, ROHS Compliant EMI FCC Parts 18, Subparts C, Class A

Rating: IP 30 Damp, Dry

Output Open/Short Protection
Min. Starting Temp: - 40° C
Max. Case Temp: 90° C

Typical Efficiency: 87%

Input Voltage range: + 10%
Output Load range + 5%
Input Frequency: + 50/60HZ
THD: + 20%
Power Factor Min: + 0.90

Remote Wiring Distance Full Load: 18AWG -18 ft

Terminal Blocks

Case Size: Series E13

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice

	INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
Ī	120	0.58A	62	54	28 to 36V	1 to 1.5A	NM1500C54WSD
	347	0.19A					

LIMITED WARRANTY


5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer

0-10V Dimmer Compatibility Chart

	.,		
LEVITON	LUTRON		
DS710-10Z	NFTV		
	DVTV-WH		

VR: Control Output 1.0 to 1.5A





WARNING: Always Disconnect Power Before Handling.

Case Should be Grounded. Install in Accordance
with National and Local Electrical Codes.

L W H ML
Series E13 314mm 34mm 27.5mm 301mm
Case Size: 12.36inch 1.34inch 1.08inch 11.85inch

1500 Marine Drive, #200 North Vancouver, BC V7P 1T7

TEL: 604-904-9533 FAX: 604-904-9634

EMAIL: sagelighting@shaw.ca www.sagelighting.com

